



SINGLE-FAMILY RESIDENTIAL

	HOLLOW CORE (H8/H4)		PARTICLE CORE (P20)		SCL CORE		FIRE CORE						
	SD10	LD1000	SD20	LD2000	SD35	LD3500	SD45	LD4500	SD60	LD6000	SD90	LD9000	
DOOR OPENINGS													
Bedrooms	*	*	*	*									
Laundry	*	*	*	*									
Bathrooms	*	*	*	*									
Closets & Pantry	*	*	*	*									
House to Garage			*	*	*	*	*	*	*	*			
ATTRIBUTES													
WDMA Performance Rating													
Extra-Heavy Duty		* 3		* 3		* 3		* 3		* 3			
Heavy Duty													
Standard Duty	* 3		* 3		* 3		* 3		* 3				
Life & Safety													
(Positive or Neutral Pressure) Fire Rating			20 MIN	20 MIN	20 MIN	20 MIN	45 MIN	45 MIN	60 MIN	60 MIN	90 MIN	90 MIN	
STC Acoustic Rating			STC 33	STC 32		STC 35					STC 32	STC 32	
Door Face Options													
High Pressure Decorative Laminate													
Wood Veneer	*	*	*	*	*	*	*	*	*	*			
Primed Medium Density Overlay		*		*		*		*		*			
Primed MDF/HDF	*	*	*	*	*	*	*	*	*	*			
Primed Molded Panel	*		*		*		*		*				
Wet Finish MDF	*		*		*		*		*				
Vertical Edge Options													
Hardwood	2	1	2	1	2	1	2	1	2				
Laminate													
Veneer		2		2		2		2					
Softwood	1		1		1		1		1				
Finger-joint	2		2		2		2		2				
MDF	1												
Environmental Preferred Options													
Rapidly Renewable								LD45AG					
No Added Urea-Formaldehyde	*	*	*	*	*	*	*	*	*	*			
FSC Certified CoC				*		*		LD45AG					
Recycled Material	*	*	*	*	*	*	*	*	*	*			
Warranty													
Lifetime		*		*		*		*		*			
One year	*		*		*		*		*				

Key
* - Available
1 - Typical Product Offering
2 - Optional Product Offering
LD45AG - Only available in a single swing application up to a 4'0 x 8'0 opening size.
* 3 - Optional blocking is required when surface applied hardware is mounted with wood screws in lieu of thru bolts.
20, 45, 60 & 90 MIN - Rated in Neutral & Positive Pressure (as required by local code)